PATENT COOPERATION TREATY

PCT

REC'D	2	0	OCT	2005
14/100				PC:

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference							
Case E-2261/04		CTION See Form PCT/IPEA/416					
International application No. International filing date PCT/IB2004/002219 06.07,2004		lay/month/year)	Priority date (day/month/year) 09.07.2003				
International Patent Classification (IPC) or national classification and IPC F04B35/00, F03G7/08							
Applicant ERRIU, Fernando							
This report is the international pre- Authority under Article 35 and tra	 This report is the international preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36. 						
2. This REPORT consists of a total	of 4 sheets, including th	is cover sheet.					
3. This report is also accompanied	by ANNEXES, comprisin	g:					
a. 🗵 sent to the applicant and to the International Bureau) a total of 4 sheets, as follows:							
sheets of the description, claims and/or drawings which have been amended and are the basis of this report and/or sheets containing rectifications authorized by this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions).							
sheets which supersede earlier sheets, but which this Authority considers contain an amendment that goes beyond the disclosure in the international application as filed, as indicated in item 4 of Box No. I and the Supplemental Box.							
b. (sent to the International Bureau only) a total of (indicate type and number of electronic carrier(s)), containing a sequence listing and/or tables related thereto, in computer readable form only, as indicated in the Supplemental Box Relating to Sequence Listing (see Section 802 of the Administrative Instructions).							
4. This report contains indications relating to the following items:							
☑ Box No. I Basis of the op	pinion						
☐ Box No. II Priority							
☐ Box No. III Non-establishr	ment of opinion with rega	rd to novelty, inventive	step and industrial applicability				
☐ Box No. IV Lack of unity of	f Invention						
Box No. V Reasoned state applicability; ci	Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement						
☐ Box No. VI Certain docum							
Box No. VII Certain defect			•				
☐ Box No. VIII Certain observ	ations on the internation	al application					
Date of submission of the demand		Date of completion of the	nis report				
09.05.2005		21.10.2005					
Name and mailing address of the International		Authorized Officer					
preliminary examining authority: European Patent Office - P.B. 5818 Patentlaan 2 NL-2280 HV Rijswijk - Pays Bas Tel. +31 70 340 - 2040 Tx: 31 651 epo nl Fax: +31 70 340 - 3016		Ingelbrecht, P	and the same of th				
		Telephone No. +31 70	340-2256				

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No. PCT/IB2004/002219

_	Box No. I Basis of the report					
1.	With regard to the language , this report is based on the international application in the language in which it was iled, unless otherwise indicated under this item.					
	which is the language of a tr international search (und publication of the internation	slations from the original language into the following language, anslation furnished for the purposes of: ler Rules 12.3 and 23.1(b)) tional application (under Rule 12.4) examination (under Rules 55.2 and/or 55.3)				
2.	 With regard to the elements* of the international application, this report is based on (replacement sheets whice have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report): 					
	Description, Pages					
	1-14	as originally filed				
	Claims, Numbers					
	1-15	received on 09.05.2005 with letter of 09.05.2005				
	Drawings, Sheets					
	1/7-7/7	as originally filed				
	a sequence listing and/or an	y related table(s) - see Supplemental Box Relating to Sequence Listing				
3.	 □ The amendments have resulted in the cancellation of: □ the description, pages □ the claims, Nos. □ the drawings, sheets/figs □ the sequence listing (specify): □ any table(s) related to sequence listing (specify): 					
4.	☐ This report has been establiched not been made, since they he supplemental Box (Rule 70.2(c)) ☐ the description, pages ☐ the claims, Nos. ☐ the drawings, sheets/figs ☐ the sequence listing (specific parts) ☐ any table(s) related to see	ecify):				
	* If item 4 applies so	ome or all of these sheets may be marked "supergoded"				

Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

4-15

1. Statement

Novelty (N) Yes: Claims

No: Claims 1-3

Inventive step (IS) Yes: Claims 4-15

No: Claims 1-3

Industrial applicability (IA) Yes: Claims 1-15

No: Claims

2. Citations and explanations (Rule 70.7):

see separate sheet

Re Item V

Reasoned statement with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Reference is made to the following documents:

D9: US-A-4 409 489 (HAYES) 11 October 1983 (1983-10-11)

- 2. The present application does not meet the criteria of Article 33(1) PCT, because the subject-matter of claim 1 is not new in the sense of Article 33(2) PCT.
- 2.1 The document D9 discloses (the references in parentheses applying to this document, figures 1-3): a fluid device for recovery of the kinetic energy of vehicles, comprising an intake pipe (131), a delivery pipe (121), and a pumping unit (140,141,142), which is connected to said intake pipe and to said delivery pipe for sending fluid under pressure from said intake pipe to said delivery pipe, at least one actuating element (200), which is set along a road or railway course of a road or railway infrastructure for land vehicles, is connected to said pumping unit and can move between a position of unloading and a position of loading, in which said at least one actuating element (200) is adapted to be surmounted by a vehicle (B) travelling along said road or railroad course, wherein said actuating element is elastically deformable and has a contact surface in contact with said vehicles and substantially aligned to said road or railroad course.
- 3. Document D9 further discloses all the features of claims 2 and 3 which therefore also do not fulfill the requirements of Article 33(1) PCT
- 4. The combination of the features of dependent claim 4 is neither known from, nor rendered obvious by, the available prior art, and therefore claim 4 fulfills the requirements of Articles 33(1),(2) and (3) PCT.
- Claims 5-15 are considered dependent on claim 4 and as such also meet the requirements of the PCT with respect to novelty, inventive step and industrial applicability.

1

PCT APPLICATION NO. PCT/IB2004/002219 in the name of Fernando ERRIU

Claims

- 1. A fluid device (1; 20; 40; 50; 60; 70; 80; 90; 90'; 90'') for recovery of the kinetic energy of vehicles, comprising an intake pipe (13), a delivery pipe (15), and a pumping unit (7; 22), which is connected to said intake pipe (13) and to said delivery pipe (15) for sending fluid under pressure from said intake pipe (13) to said delivery pipe 10 (15), at least one actuating element (5; 22; 44; 52; 62; 76; 108), which is set along a road or railway course (3; 75) of a road or railway infrastructure (3a; 71) for land vehicles, is connected to said pumping unit (7; 22) and can move between a position 15 of unloading and a position of loading, in which said at least one actuating element (5; 22; 44; 52; 62; 76; 108) is adapted to be surmounted by a vehicle travelling along said road or railroad course (3; 75), said device being characterized in that said . 20 108) is elastically actuating element (22; 76; deformable and has a contact surface (26) in contact with said vehicles and substantially aligned to said road or railroad course (3; 75)...
- The device according to Claim 1, characterized in that said surface of contact (26) is substantially plane, and in that said actuating element (22; 76; 108) comprises end portions (27) longitudinally set opposite to one another and rigidly connected to said road or railroad course (3; 75).
 - 3. The device according to Claim 2, characterized in

that said actuating element (22) comprises a membrane, and defines, at the top, a first variable-volume chamber (23) connected to said intake line (13) and said delivery line (15).

- 5 4. The device according to Claim 3, characterized in that it comprises a honeycomb structure (103) for pumping connected to said intake line (13) and said delivery line (15), which defines a multiplicity of second variable-volume chambers (109) delimited, at the bottom, by a supporting wall (100, 110) and cooperating, at the top, with said actuating element (22).
- according to Claims 3 and The device 5. characterized in that said honeycomb structure (103) is set inside said first chamber (23), and in that 15 each of said second variable-volume chambers (109) is delimited by rigid side walls (107), which come out of said supporting wall (100) and, at the top, from a deformable head membrane (108) connected in a fluidtight way to said side walls (107) and co-operating 20 with said actuating element (22).
 - 6. The device according to Claim 5, characterized in that said second variable-volume chambers (109) are delimited at the sides by a multiplicity of rigid separating walls (111), which are hinged to said actuation element (22) and to the supporting wall (110).
- 7. The device according to any one of the preceding claims, characterized in that said device is supported, at the bottom, by a base (101), which has a plurality of intake tanks or chambers (102) that

25

are fluid-connected to one another by said intake line (13).

- 8. The device according to any one of the preceding claims, characterized in that it comprises an elastic 73), which co-operates with said (24; element actuating element (22; 76) and is designed to reestablish said unloading position.
- 9. The device according to any one of Claims 1 to 8, characterized in that said road infrastructure (3a)
- is a street. 10

5

15

25

- 9. The device according to any one of claims 3 to 8, characterized in that said road infrastructure (71) is a railroad line comprising sleepers (74), in that said road course (75) comprises tracks, in that said actuating element (76) comprises rails and in that said membrane (22) functionally cooperates with said rails.
- 10. The device according to any one of Claims 1 or 2, characterized in that said road infrastructure (71)
- railroad, comprising a bed and (73) a 20 is multiplicity of sleepers (74) supported by said bed (73), in that said actuating element (76) comprises rails connected to said sleepers (74) and in that said pumping unit (7) is functionally connected to at least one of said sleepers (74)...
- 11. The device according to Claim 10, characterized in that it comprises an oscillating actuating member (62) connected to one of said sleepers (74) and said
 - pumping unit (7).
- 12. The device according to any one of the preceding 30

[IB0402219

claims, characterized in that it comprises a unit for generation of electric power (17, 18) connected to said delivery line (15).

- 13. The device according to any one of the preceding claims, characterized in that said fluid is 5 hydraulic.
 - 14. The device according to any one of the preceding claims, characterized in that said fluid follows a closed circuit (150).
- 15. The device according to any one of the preceding 1.0 claims, characterized in that it comprises rigid elements (105, 107a) disposed below said actuating element (5; 22; 44; 52; 62; 76; 108) and supporting said actuating element (5; 22; 44; 52; 62; 76; 108) 15 in said loading position.